

2 LAYERS NUDURA
CEILING TECHNOLOGY

PLASTER BOARD

DAMP PROOF COURSE/
AIR SHIELD MEMBRANE
CONTINUOUS UNDER
TOP PLATE EXTENDED
TO COMPLETE AIR
SHIELD WITH CEILING
TECHNOLOGY

ROOF SHEATHING AS
SPECIFIED

RAFTER

SOFFIT/FASCIA (TYPICAL)

38x140mm SILL PLATE
ANCHORED TO CONCRETE AS
PER CODE

HORIZONTAL/VERTICAL
REINFORCEMENT AS
SPECIFIED BY LOCAL
PRESCRIPTIVE OR
ENGINEERING DESIGN

NUDURA STANDARD
152mm FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

28x89mm
FURRING STRIP
(FACTORY
EMBEDDED)
400mm ON
CENTRE

200x200mm
VAPOR BARRIER
MEMBRANE
CONTINUOUS

PLASTER BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

STANDARD 152mm FORM UNIT
ROOF RAFTER DETAIL
AT TOP PLATE
DAMP PROOF COURSE
EXTERIOR FINISH AS SPECIFIED

REV. NO.
000

DATE:
NOV 2009

DRAWN BY:
K. STILL

DWG NO.

CE-14

SCALE:
1 : 8